

BiOWN[®]

ARMATURER



BiOWNLIGHT

TEKNIK



www.brightel.se











LpS / TIL AWARDS
(2018)
NOMINEE

PRODUCT OF THE YEAR
GOLD MEDAL
Lithuanian Confederation of Industrialists
LITHUANIA 2018



Enabled
Licensing Program for LED
Luminaires and Retrofit Bulbs
Member
BiOWN

SPECIFIKATIONER

 Modell	KONTOR / HEM / SKOLA					MEDICINSKT				INDUSTRI				FRISTÅENDE	
Typ	SL-B6-2765-1-S SL-B6-2765-1-SM	SL-B6-2765-1-R1	SL-B6-2765-1-R2	SL-B6-2765-1-R3	SL2-B6-2765-2-S	SL-B6-1865-3-S SL-B6-1865-3-SM	SL2-B6-1865-3-R1	SL2-B6-1865-3-R2	SL2-B6-1865-3-R3	SL-B6-2765-1-S SL-B6-2765-1-SM	SL-B6-2765-1-R1	SL-B6-2765-1-R2	SL-B6-2765-1-R3	SL-B6-2765-1-ST4	SL-B6-1865-3-ST4
Bild															
Armatur storlek	552 x 418 x 75mm	595 x 595 x 75mm	595 x 595 x 105 mm	620 x 620 x 105 mm	1150 x 418 x 75 mm	552 x 418 x 75mm	595 x 595 x 75mm	595 x 595 x 105 mm	620 x 620 x 105 mm	552 x 418 x 75mm	595 x 595 x 75 mm	595 x 595 x 105 mm	620 x 620 x 105 mm	ca 874 x 2340 mm	
Vikt	3.9 kg	5.8 kg	5.8 kg	5.8 kg	ca 7.5 kg	3.9 kg	5.8 kg	5.8 kg	5.8 kg	3.9 kg	5.8 kg	5.8 kg	5.8 kg	ca 16.5 kg	
LED kanaler: 6	+	+	+	+	+	+	+	+	+	+	+	+	+	+	
LED antal	208	208	208	208	416	216	216	216	216	208	208	208	208	208	216
Automatisk färdighets aktivitet	+	+	+	+	+	+	+	+	+	+	+	+	+	+	
CRI Ra>95 R9>90	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Flimmerfri	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Bländskydd (tillval)	+					+				+				+	
CCT	2700K ÷ 6500K				2700K ÷ 6500K	1800K ÷ 6500K				2700K ÷ 6500K				2700K ÷ 6500K	1800K ÷ 6500K
Kontroller: Tryckknappar, PC, Mobilapp	+				+	+				+				+	
Initialt ljusflöde max.*	5600 lm					5000 lm				5600 lm				5600 lm	5000 lm
Installations effekt	80W ± 5%				92W ± 5%	82W ± 5%				80W ± 5%				80W ± 5%	82W ± 5%
Initial strömförbrukning max	68W ± 5%				80W ± 5%	70W ± 5%				68W ± 5%				68W ± 5%	70W ± 5%
Huvudspänning	~230V 50Hz; ~120V 60Hz					~230V 50Hz; ~120V 60Hz				~230V 50Hz; ~120V 60Hz				~230V 50Hz; ~120V 60Hz	
Driftstemperatur	10 ÷ 40° C					10 ÷ 40° C				10 ÷ 40° C				10 ÷ 40° C	
IP klass	IP20; IP44					IP20; IP44				IP20; IP44				IP20; IP44	
CE, ROHS	+					+				+				+	
Garanti: 5 år (begränsad)	+					+				+				+	
 www.biownlight.com	KONTOR / HEM / SKOLA					MEDICINSKT				INDUSTRI				FRISTÅENDE	